



China abec 5 Bearing Supplier



Origin NSK HPS 6208 ZZ NSK Deep Groove Ball Bearings 6208 ZZC3 NSK Bearing 6208

Bearing No. 6208

6208 Bearing 2D drawings and 3D CAD models

| | |
|-------------------------------|--------------------------|
| Size | 40x80x18 mm |
| Bore Diameter | 40 mm |
| Outer Diameter | 80 mm |
| Width | 18 mm |
| d | 40 mm |
| D | 80 mm |
| B | 18 mm |
| C | 18 mm |
| r min. | 1,1 mm |
| da min. | 46,5 mm |
| da max | 50,5 mm |
| Da max. | 73,5 mm |
| ra max. | 1 mm |
| Weight | 0,366 Kg |
| Basic dynamic load rating (C) | 29,1 kN |
| Basic static load rating (C0) | 17,9 kN |
| (Grease) Lubrication Speed | 8 500 r/min |
| (Oil) Lubrication Speed | 10 000 r/min |
| Category | Single Row Ball Bearings |
| Inventory | 0.0 |
| Manufacturer Name | NSK |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 0.405 |
| EAN | 0029176014765 |
| Product Group | B00308 |



China abec 5 Bearing Supplier

| | |
|---------------------------------|--|
| Enclosure | Open |
| Precision Class | ABEC 1 ISO P0 |
| Maximum Capacity / Filling Slot | No |
| Rolling Element | Ball Bearing |
| Snap Ring | No |
| Internal Special Features | No |
| Cage Material | Steel |
| Internal Clearance | C0-Medium |
| Inch - Metric | Metric |
| Long Description | 40MM Bore; 80MM Outside Diameter; 18MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features |
| Category | Single Row Ball Bearing |
| UNSPSC | 31171504 |
| Harmonized Tariff Code | 8482.10.50.68 |
| Noun | Bearing |
| Keyword String | Ball |
| Manufacturer URL | http://www.nskamericas.com |
| Manufacturer Item Number | 6208 |
| Weight / LBS | 0.363 |
| Outside Diameter | 3.15 Inch 80 Millimeter |
| Outer Race Width | 0.709 Inch 18 Millimeter |
| Bore | 1.575 Inch 40 Millimeter |
| SRI | 6.16 |
| hidYobi | 6208 |
| LangID | 1 |
| D_ | 80 |
| SREX | 0.025 |
| B_ | 18 |



China abec 5 Bearing Supplier

| | |
|------------|-------------|
| da min | 46.5 |
| hidTable | ecat_NSRDGB |
| Oil rpm | 10000 |
| SRE | 6.16 |
| mass | 0.366 |
| GRS rpm | 8500 |
| ra | 1 |
| SRIX | 0.025 |
| D_a | 73.5 |
| SRIN | -0.025 |
| C0 | 17.9 |
| fo | 14 |
| SREN | -0.025 |
| DE_ | 71.906 |
| Prod_Type3 | DGBB_SR_OT |
| DA_ | 11.906 |
| bomp | 0 |
| Z_ | 9 |
| yobi | 6208 |
| C_conv | 29100 |
| ALPHA_ | 0 |
| SDM_ | 60 |
| r | 1.1 |
| KBRG | 6101 |
| SBRG | 2 |
| DI_ | 48.094 |