



## China abec 5 Bearing Supplier



6312 N/Zn/Nr/Znr/K- O&Kai Z1V1 Z2V2  
Z3V3 ISO Deep Groove Ball Bearing SKF NSK  
NTN NACHI Koyo OEM

Bearing No. 6312

6312 Bearing 2D drawings and 3D CAD models

Size	60x130x31 mm
Bore Diameter	60 mm
Outer Diameter	130 mm
Width	31 mm
d	60 mm
D	130 mm
B	31 mm
C	31 mm
r min.	2.1 mm
da min.	72 mm
Da max.	118 mm
ra max.	2.0 mm
Weight	1.70 Kg
Basic dynamic load rating (C)	82 kN
Basic static load rating (C0)	52 kN
(Grease) Lubrication Speed	5100 r/min
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	NACHI
Minimum Buy Quantity	N/A
Weight / Kilogram	0
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1   ISO P0



## China abec 5 Bearing Supplier

Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	60MM Bore; 130MM Outside Diameter; 31MM Outer Race Width; Open; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage
Other Features	Deep Groove
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	<a href="http://www.nachiamerica.com">http://www.nachiamerica.com</a>
Bore	2.362 Inch   60 Millimeter
Inner Race Width	0 Inch   0 Millimeter
Outside Diameter	5.118 Inch   130 Millimeter
Outer Race Width	1.22 Inch   31 Millimeter
Bore Type	Cylindrical Bore
Configuration	Single Row
Bore Size	60 mm
Width	31 mm
Fillet Radius/Chamfer	2.1 mm
Dynamic Load Rating	82,000 N



## China abec 5 Bearing Supplier

Static Load Rating	52,000 N
Limiting Speed - Grease	5,400 rpm
Limiting Speed - Oil	6,300 rpm
Factor $f_0$	13.2
Radial Clearance	0.008 to 0.028 mm
$d_a$ (min)	72 mm
$D_a$ (max)	118 mm
$r_a$ (max)	2 mm